

FORMPAK INC

SCREW FEEDER IOM 2021 EDITION

DISCLAIMERS:

NOT ALL ITEMS IN THIS MANUAL ARE ON EVERY SYSTEM.

SYSTEM CONFIGURATIONS VARY PER CUSTOMER ORDERS & SPECS.

ANY MODIFICATIONS TO THE EQUIPMENT WITHOUT APPROVAL OF FORMPAK ENGINEERING WILL
RESULT IN VOIDING ANY WARRANTY.

Operation Hours

Monday – Friday 8:00AM–5:00PM CST

Contacts at FormPak

Mike Owens Ext 402
Sales / General Questions
Email: mike@formpakinc.com

Larry Markos, P.E. Ext 403
Engineering / Technical Support / Maintenance
Email: larry@formpakinc.com

Robert Contreras Ext 405
Operations Manager Email:
Email: robert@formpakinc.com

Joseph Beckerman Ext 414
Electrical / Controls Email:
Email: josephb@formpakinc.com


Ken Poorman Ext 412
Purchasing / Parts Email:
Email: kenp@formpakinc.com

Fax : 314-475-3201

Approved By:	Approved By:	Document Name:	Rev:
Lucas Pulley	Amanda Michaels	111-CM-SF	0.0

Screw Feeder

FormPak's Screw Feeder is designed to meter feed material that has been discharged from a bulk bag, so it can be conveyed or integrated into a process. It is a simple design, requiring minimal maintenance, yet very effective. The tube comes in usual sizes of 4" or 3" OD, but can become more custom. The auger itself has a standard, however like most FormPak machinery, it can vary per the customer material and/or needs of the unit design.



Gearbox lubrication is for life, as long as there are no leaks. Leaks should be addressed as soon as possible. A leaking seal is often a sign of a failed bearing.

Motor rotation direction is not important, but motor voltage is. Be sure the electrician wires the motor for the correct three phase voltage.

Maintenance daily inspections should be done over all bolts & nuts to verify all are tight and secure. The Auger and Tube should also be inspected to look for wear and tear. Most commonly this will be seen on the ends of the tube and auger due to the rotation of the machine. Lastly, welds on the exterior and interior are to be looked over for visible cracks and/or defects. This is not common, but over time this can occur depending on material, amount of usage, and improper maintenance over the auger